

CSI-C-11 | ConditionSensor Interface



Features:

- Ability to view in real-time measured contamination results via Wireless Connection or *Bluetooth*® wireless technology with the FluMoS mobile App.
- Storage of the measured data directly on the CSI-C-11.
- Easily interface digital sensors into existing LAN network.
- Direct connection of up to two (2) SMART sensors via M12x1 connectors.
- Integral bracket allows for easy installation on existing machines.
- Usable with FluMoS mobile App.

Markets:

- Construction
- Agricultural
- Test Benches
- Industrial Systems
- w/ Filter Unit
- Power Units
- Mining

Specifications:

- **HSI Interface:**
Schroeder Sensor Interface for digital coupling sensors
- **Ethernet**
10 Base-T / 100 Base - TX
W-LAN (HSI only)
2,4 GHz, IEEE 802.11 b/g/n:
Protocol: HSI TCP/IP (Port 49322)
Modbus® TCP (Port 502)
- **Operating Temp. Range:**
-13°F to 185°F (-25°C to 85°C)
- **Storage Temp. Range:**
-22°F to 185°F (-30°C to 85°C)
- **Relative humidity:**
0 ... 70%, non-condensing
- **CE marked:**
EN 61000-6-2, EN 61000-6-4
- **Weight:**
.79 lb. (~ 360 g)